

ALUMACRAFT

LUNKER 165 CS LUNKER 165 tiller



LUNKER 165	CS	Tiller
DIMENSIONS		
LENGTH	16'6" 5.0m	16'6" 5.0m
WIDTH—Maximum beam	76" 1.92m	76" 1.92m
DEPTH—Maximum/to floor	35"/22" .88m/.54m	35"/22" .88m/.54m
TRANSOM—Width/height	73"/20" 1.85m/.51m	73"/20" 1.85m/.51m
CAPACITIES		
HORSEPOWER—Maximum	50 HP 37kw	40 HP 30kw
CAPACITY—Persons/lbs.	5/1235# 5/560kg	5/1235# 5/560kg
WEIGHT—Lbs.	700# 317kg	660# 299kg
DEEP-V 2XB BOW HULL		
THICKNESS bottom/sides	.080"/.065" 2.0mm/1.7mm	.080"/.065" 2.0mm/1.7mm
2XB BOW—2nd plate	.060"	.060"
SEATS		
Driver seat is stationary w/height adjust; slider (CS)		
SEATS	2	2
PEDESTALS/SOCKETS	2/4	2/3

STEERING & CONSOLE

- CS: Console w/single cable no-feedback steering; removable windshield
- TILLER: Tiller steering

LIVEWELL

SIDE LIVEWELL—gallons—w/h/l
Aerated, bait system

13 gal—9"x13"x 32"
49L—23cm/33cm/81cm

CONSTRUCTION FEATURES

- BOW CASTING PLATFORM—w/pedestal socket
- AFT CASTING PLATFORM—w/pedestal socket (CS)
- AQUEDUCT TRAY
- WIREWAY TUBE, bow to stern
- EXTRAS—Grab handle at each seat location

STORAGE, ELECTRICAL, ETC.

- STORAGE—Lockable bow storage compartment, lockable starboard rod storage up to 8'
- BATTERY STORAGE—1 forward, 1 aft starting
- ELECTRICAL—Circuit breakers
- TROLLING SYSTEMS—12V bow outlet
- LIGHTS—Stowable running lights
- BILGE PUMP—Manual

OPTIONAL EQUIPMENT

- TROLLING MOTOR—Minn Kota
- GRAPH—Lowrance liquid crystal
- VINYL FLOOR
- SEAT—Extra seat and pedestal
- COVERS—Mooring cover

PAINT & FLOOR

- Oxford White or Aztec Gray
- Midnight Star Gray carpet

NEW FOR 2008

- Low back Tempress seats
- 13 gallon livewell
- Graphics

